

shr411MXGE

SHR 10GigE



The high resolution SHR series offers outstanding image quality. This is made possible by the excellent physical characteristics of large pixels in large format sensors. The thermally highly optimized housing guarantees highest optical precision. The large M72 lens mount can be adapted to any lens. The economical and high-performance 10 GigE interface offers high data transfer speeds of up to 1.1 GB/s for these large images. A special frame grabber is not required.

Technical Highlights

- > User defined shading correction
- > Automatic and user defined pixel correction
- > Extremely low noise
- > Excellent dynamic range
- > high performance 10GigE interface
- > Integrated 4-channel LED strobe controller
- > Industrial TTL-24V I/O Interface with SafeTrigger, programmable logic functions, sequencers and timers, RS232

SHR Series

shr411MXGE

Resolution [MP]	151 MP
Resolution (h x v)	14192 x 10640 px
Frame rate (max.)	6.1 fps
Chroma	mono
Interface	10GigE (RJ-45)

Sensor

Sensor	IMX411ALR
Manufacturer	Sony
Sensor type	Area CMOS
Shutter type	rolling shutter
Sensor size (h x v)	53.36 x 40.01 mm
Optical diagonal	66.69 mm
Sensor format	Medium Format
Pixel size (h x v)	3.76 x 3.76 μm

Camera

Exposure modes	MANUAL;AUTO;EXTERNAL
Trigger modes	INTERNAL;SOFTWARE;EXTERNAL
Exposure time (min)	60 μs
Exposure time (max)	1 sec (external ∞)
Pixel format / max	mono8, mono12, mono16 / 16 bit
Gain modes / max	manual, auto / 36 dB
S/N ratio (max)	46.7 dB (dep. on environment)
Dynamic range (max)	82 dB (dep. on environment)
Internal memory	512 MB SDRAM

Feature Set

LUT	yes
Offset	yes
Binning	yes
Image flip	yes
Shading correction	yes (external)
Defect pixel correction	yes
Sequencer	yes
POE	yes (POE+)(optional)


Housing

Lens mount	M72x0,75
Dimensions (w x h x d)	80 x 80 x 83 mm
Weight	580 g
Operating temperature (housing)	-10 to 65 °C
Ambient humidity	10 to 90 % (non-condensing)
Protection class	IP30
Filter-/Coverglass	Borofloat B270i - AR coating

I/O-Interfaces

Input up to 24V	2 x
Input OPTO	1 x
Output open drain	4 x
I/O RS-232	1 x
Power supply	10 to 25 V (DC)
Power consumption	17 W (dep. on operating mode)


Dimensions [mm]



Pinout Mating Connector

Hirose 12 Pin	1	VIN - (GND)	7	OUT 1 (open drain)
	2	VIN + (10 V to 25 V DC)	8	OUT 2 (open drain)
	3	IN 4 (RXD RS232)	9	IN 3 + (opto In +)
	4	OUT 4 (TXD RS232)	10	IN 3 - (opto In -)
	5	IN 1 (0-24V)	11	OUT 3 (open drain)
	6	IN 2 (0-24V)	12	OUT 0 (open drain)

Spectral Response *



* Sensor data — excludes camera cover- or IR-cut filter characteristics

